

X-WEATHER WARRIOR

"An Exceptional Synthetic Underlayment Designed to Replace Asphalt Saturated Felts on Your Roofing Projects"



- **Advanced Engineering...** providing an affordable secondary water-shedding barrier for your shingle roof system.
- **Inorganic Construction...** 100% synthetic construction offers long term moisture protection - doesn't absorb water and is inert to mold growth.
- **Advanced Surface Technologies...** WarriorWalk (top) and WarriorGrip (back) create incredible walkability.
- **Improves Project Outcome...** rolls out flat and does not wrinkle, eliminating customer callbacks.
- **Easier Installation...** 33% more coverage per pass across the roof (vs 36" wide rolls).
- **Superior Performance...** designed to perform under extreme weather conditions.
- **Durable...** synthetic construction resists tearing during roof installation - UV stabilized to resist UV degradation up to 30 days.



"Non-Woven top and Anti-Slip reverse side offers dynamic steep slope traction"

DESCRIPTION

Xtreme Weather Warrior Synthetic Roof Underlayment is a synthetic roof-deck protection designed and manufactured to replace asphalt saturated felt in sloped roof system construction.

USES

A cost effective roofing underlayment used beneath fiberglass and asphalt shingles, shakes, stone coated steel roofing shingles and synthetic slate.

STORAGE

Always store rolls upright on pallets (or in the cradled pallet the rolls are shipped on) and in a dry protected area.

AVAILABILITY

Xtreme Weather Warrior Felt is available throughout the United States. Check with your local representative.

COMPLIANCE: CODES

- Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV
- Performance characteristics meet or exceed ASTM D226 – Type I, II
- Meets the requirements of ICC-AC-188 – Intertek / WH #CRR 1115
- Texas Department of Insurance listed CRR - #1115
- UV Exposure – 30 days
- U.L. Classified as a Prepared Roofing Accessory

PHYSICAL INFORMATION

- Roll Size: 48" X 250'
- Material Per Roll: 1000 sq. ft.
- Squares Per Roll: 10 squares
- Weight Per Roll: 19 lbs
- Rolls Per Pallet: 64 rolls
- Wt Per Pallet: 1,266 lbs
- Limited Warranty: 15 Years

SPECIFICATIONS (meets or exceeds applicable standards)

	Standard	X-Weather Warrior
Permeability	ASTM E96	.06
Water Transmission	ASTM D4869	pass
Pliability	ASTM D226	pass
Tear Strength	ASTM D4533	20 lb MD / 20 lb CD
Tensile Strength	ASTM D751	50 lb MD / 50 lb CD
Elongation	ASTM D751	20% MD / 20% CD
Wt Per Square	ASTM D5261	1.9 lbs
Nominal Thickness	ASTM D5261	6 mils
Range of Temperature		- 40°F to 240°F
Fire Rating UL Class A	ASTM E108	pass