



CONTINENTAL MATERIALS, INC

Fasteners • Asphalt • Underlayments • APP • Fiberboard


*"Quality Manufactured
Components...
Making Construction
Systems Perform Better
Since 1958"*

No-SmellTM Roofing Asphalt

visit us at www.continentalmaterials.com

*"Why Mask
The Odor...
When You Can
Encapsulate It!"*

- **No more odor complaints...** Patented XyClene™ Technology encapsulates the low-end asphaltenes (that produce odor) making the asphalt smell virtually undetectable to workers, building occupants, and neighbors
- **Eliminates scheduling hassles...** Roofing can be performed even if building is occupied
- **Superior to competitive technologies...** That only mask the odor (like using perfume) or that have an offensive smell
- **Meets or exceeds ASTM D312-16...** The industry standard for high quality asphalt for built-up roofing
- **Two packaging options...** Available in convenient cartons or bulk
- **Proven performance...** Independently tested to assure long term asphalt integrity
- **Ready to use...** The No-Smell™ is factory mixed to assure maximum effectiveness; no messy or dangerous additives need to be added at the kettle



No-Smell™ Asphalt

"Why Mask The Odor... When You Can Encapsulate It!"



Cartons

- **ASTM and EVT data on every carton...**
Every carton is clearly marked for convenience
- **Weather Seal™ pallet cover...** Protects against ice, water, and debris for up to 6 months; also keeps the asphalt cartons cool (and pallets stable) in hot weather
- **Superior storability...** UV-resistant protective cover is perfect for the warehouse or at the job site



Bulk

- **Improves productivity...**
No time wasted melting packaged asphalt
- **Economical...**
Less expensive to use (on a total acquisition cost basis) than packaged asphalt



Weather Seal™ pallet cover protects against the elements for up to 6 months!



Physical Properties/Specifications (All CMI asphalt meets or exceeds ASTM D312-16 requirements)									
	ASTM Test Method	Type I		Type II		Type III		Type IV	
		Min	Max	Min	Max	Min	Max	Min	Max
Softening Point	D-36	135	151	158	176	185	205	210	225
Flash Point (°F)	D-92	575	-	575	-	575	-	575	-
Penetration, Units:									
at 32°F	D-5	3	-	6	-	6	-	6	-
at 77°F	D-5	18	60	18	40	15	35	12	25
at 115°F	D-5	90	180	-	100	-	90	-	75
Ductility at 77°F, cm	D-113	10	-	3	-	2.5	-	1.5	-
% solubility in trichloroethylene	D-2042	99	-	99	-	99	-	99	-

The Secret Behind Proprietary XyClene™ No-Smell Technology

Unlike cheap imitations, No-Smell™ Asphalt doesn't just contain a masking agent. Its proprietary XyClene™ formula is a true odor suppressant. It acts at the molecular level as an oxygen scavenger to retard the release of specific odor-causing compounds. The XyClene™ formula encapsulates asphaltenes, stopping the evaporation of lighter petroleum molecules and eliminating fumes. It is your best answer to asphalt roofing odors at the kettle, and more importantly, on the roof.



*"Quality Manufactured Components...
Making Construction Systems Perform Better Since 1958"*

No-Smell™ Asphalt



Virtually eliminates objectionable asphalt odors during the installation—so complaints from occupants and the neighbors disappear.

Fiberboard



Your best choice for reliable performance in asphaltic or single ply roofing systems. It's even environmentally-friendly!

Underlayments



Top quality synthetic and asphaltic underlayments at prices you can afford—and with quality that you can rely on every day.

Fasteners



Superior value has made us one of the largest and fastest-growing fastener suppliers in North America—for more than half a century!

Application Tools



Ultra-high purity, 100% cotton mops deliver long-lasting performance and the perfect balance between cost and service life.