



CONTINENTAL MATERIALS, INC

Fasteners • Asphalt • Underlayments • Fiberboard • Tools

*"Quality Manufactured
Components...
Making Construction
Systems Perform Better
Since 1958"*

Asphalt Roofing Felts

visit us at www.continentalmaterials.com

*"Top Quality
Roofing Felts
At Prices You
Can Afford!"*

- **Best Value...** Affordable price with superior quality
- **Highest Quality Asphalt...** Unlike most producers, the manufacturing facility processes its own asphalt to ensure the highest quality and consistency
- **Environmentally-Friendly Organic Core...**
Made from 100% reclaimed/recycled material (wood chips) with a minimum of 10% post-consumer content (paper)
- **Consistent Saturation...** For superior moisture resistance and code compliance
- **Versatile...** Can be used under fiberglass shingles, wood shakes, tile, and other sloped roof coverings
- **Clearly Marked Guidelines...** for easy installation
- **Nationwide Manufacturing...** for more consistent supply and ready availability



Asphalt Roofing Felts

"Top Quality Roofing Felts At Prices You Can Afford"

Best Value

- Superior Quality
- Affordable Price



Description

CMI saturated felt is a uniform, flexible felt of organic fibers, impregnated with an asphalt saturant. Line markings are placed on the top surface for ease of installation.

Uses

A roofing felt used as an underlayment beneath fiberglass and asphalt shingles, wood shakes, tiles, and other sloped roof coverings. It helps to stop leaks caused by wind-driven rain.

Storage

Always store rolls upright on pallets and in a dry protected area.

Availability

Not all felt types are available in all areas. Other asphalt roll roofing products (43# coated base sheet and mineral surface roll roofing) available in some areas. Check with your CMI representative for availability.

Physical Properties

	No. 15 Regular	No. 15 ASTM D4869 Type I	No. 15 ASTM D226 Type I	No. 30 Regular	No. 30 ASTM D4869 Type II	No. 30 ASTM D226 Type II
Width	36"	36"	36"	36"	36"	36"
Length	144'	144'	144'	72'	72'	72'
Sq. Feet / Roll	432 ft ²	432 ft ²	432 ft ²	216 ft ²	216 ft ²	216 ft ²


Specifications (meets or exceeds applicable requirements)

	No. 15 Regular	No. 15 ASTM D4869 Type I	No. 15 ASTM D226 Type I	No. 30 Regular	No. 30 ASTM D4869 Type II	No. 30 ASTM D226 Type II
Net mass per unit area of saturated felt lbs/100 sq ft	7.8	8.0	11.5	15.3	21.6	26.2
Mass of saturant min lbs/100 sq ft	3.9	4.0	6.2	8.3	12.6	15.0
Mass of de-saturated felt, min lbs/100 sq ft	3.9	4.0	5.2	6.7	9.0	10.0
Saturant in moisture free felt, by mass (% avg)	95% min	100% min	120% min	120% min	140% min	150% min
Pliability at 25C	Pass	Pass	Pass	Pass	Pass	Pass



**"Quality Manufactured Components...
Making Construction Systems Perform Better Since 1958"**

No-Smell™ Asphalt



Virtually eliminates objectionable asphalt odors during the installation—so complaints from occupants and the neighbors disappear.

Fiberboard



Your best choice for reliable performance in asphaltic or single ply roofing systems. It's even environmentally-friendly!

Underlayments



Top quality synthetic and asphaltic underlayments at prices you can afford—and with quality that you can rely on every day.

Fasteners



Superior value has made us one of the largest and fastest-growing fastener suppliers in North America—for more than half a century!

Application Tools



Ultra-high purity, 100% cotton mops deliver long-lasting performance and the perfect balance between cost and service life.