



CONTINENTAL MATERIALS, INC

Fasteners • Asphalt • Underlayments • APP • Fiberboard

*"Quality Manufactured
Components...
Making Construction
Systems Perform Better
Since 1958"*

SecureGrip PS/MAX HT™

Self Adhered Roof Underlayment

visit us at www.continentalmaterials.com

*"Premium High-Temp Self
Adhered Roof Deck Protection---
under Metal, Tile, Slate, Shakes,
and Asphalt Shingle Roofing"*

- **Engineered Construction...** extremely strong polypropylene surface with UV and weather resistive coatings that add water shedding redundancy in the roofing system while protecting the structure from damage
- **Advanced Surface Technology...** SecureWalk™ (top) creates incredible walkability
- **All Temperature Performance...** -40° F to 260° F; all climates, under all roofing styles
- **Weather-Tight Seal...** asphalt to asphalt lap system
- **Durable...** heavy synthetic surface resists tearing during roof installation - UV stabilized surface resists UV degradation up to six months
- **100% Inorganic Surface...** synthetic construction offers long term moisture protection - won't rot and is inert to mold growth
- **Non-Woven "Cool Color" Surface...** stays cool and maximizes dimensional stability
- **Premium Adhesive Formulation...** modified bitumen adhesive protects from the effects of Wind-Driven Rain, Water, Snow and Ice Damming
- **Easy Peel Dual Film Technology...** allows for quick and simple release liner removal and underlayment installation



Premium Self Adhered Roof Underlayment

"Maximum Performance, High Temperature Roof Deck Protection under Metal, Tile, Slate, Shakes, and Asphalt Shingle Roofing"

Weather-Tight Seal...

premier asphalt to asphalt lap system

CMi SECUREGRIP PS/MAX HT™
P&S SYNTHETIC ROOFING UNDERLAYMENT

PREMIUM SELF-ADHERED UNDERLAYMENT

For Protection from
Wind-Driven Rain, Water,
Snow and Ice Damming
For use under all Shingle, Shake,
Metal, Slate and Tile Roofing
For High Temperature Installation



See www.continentalmaterials.com
for complete coverage and restrictions

Water, Vapor and Premium
Secondary Water Barrier
Special Watertight
Asphalt to Asphalt Lap System
Up to Six Month UV Exposure Rated
Meets or Exceeds ASTM D1970
Class A Fire - ASTM E108
Meets Class 4 Nail Rating
All Temperature Performance
Non-Woven Synthetic Surface is Inert
to Moisture - and Mold Growth
Non-Woven Cool Grey Surface
Maximizes Dimensional Stability

Description

CMi SecureGrip PS/MAX HT Self Adhered Roof Underlayment is designed and manufactured to be a secondary water barrier in sloped roof system construction where toughness and longer exposures may be required. SG PS/MAX HT is an air, water and vapor barrier and must be installed only above properly ventilated spaces.

Uses

A superior performing self adhered roof underlayment used under metal, tile, slate, shakes, and asphalt shingle roofing.

Storage

SecureGrip PS/MAX HT should be stored at temperatures between 40° F and 90° F, upright in the original cardboard box package in a dry and properly ventilated area.

Availability

SecureGrip PS/MAX HT is available throughout the United States. Check with your local representative for product availability.

SECUREGRIP PS/MAX HT TECHNICAL DATA

Attribute	Test Standard	SecureGrip PS/MAX HT Typical Values
Surface Color		PMS "Cool Colors"
Surface Type		'Easy Walk' Non-Woven Synthetic Polymer
Reverse Side Release Surface		Silicon Treated Poly Split-Release Film
Weight per Square		20 lbs (9.1 kg)
Nail Sealability	ASTM D1970	Pass
Permeability	ASTM E96	0.034
Nominal Thickness	ASTM D5147	45 mil (1.1mm)
Tensile	ASTM D1970	MD 130 lbs/in / CD 110 lbs/in
Thermal Stability	ASTM D1970	260° F (126°C) Pass
Low Temp Flexibility	ICCAC 48	Pass
Tear Resistance	ASTM 1970	MD 165 lbf / CD 150 lbf
Adhesion to Plywood	ASTM D903	14.5 lbs/ft
Fire Resistance	ASTM E108	Class A

SECUREGRIP PS/MAX HT ROLL SPECIFICATIONS

Length Per Roll	66.7' (20.3m)	Rolls Per Pallet	25
Width Per Roll	36" (0.914m)	Pallet Weight	1,100 lbs (499 kg)
Weight Per Roll	40 lbs (18.1 kg)	UV Resistance	180 days
Gross Roll Size	200 sq ft (18.6 sq m)		

Installation Temperature: 40° F (4.4° C) and above

Limited Warranty: Lifetime

Enhanced Slip Resistant Surface: SecureWalk Technology



Made in India



**"Quality Manufactured Components...
Making Construction Systems Perform Better Since 1958"**

No-Smell™ Asphalt



Virtually eliminates objectionable asphalt odors during the installation—so complaints from occupants and the neighbors disappear.

Fiberboard



Your best choice for reliable performance in asphaltic or single ply roofing systems. It's even environmentally-friendly!

Underlayments



Top quality synthetic and asphaltic underlayments at prices you can afford—and with quality that you can rely on every day.

Fasteners



Superior value has made us one of the largest and fastest-growing fastener suppliers in North America—for more than half a century!

Application Tools



Ultra-high purity, 100% cotton mops deliver long-lasting performance and the perfect balance between cost and service life.