

SecureGripPRO™ Synthetic Roof Deck Protector

Great Value
Engineered for builders and contractors - providing an affordable secondary water-shedding barrier for roof systems.

“Excellent Replacement for Traditional #15 Felt on your Roofing Projects!”

- **Highly Engineered...** for builders and roofers to provide an effective secondary water-shedding barrier for shingle roof systems.
- **Inorganic Construction...** 100% synthetic construction offers long term moisture protection - doesn't absorb water and is inert to mold growth.
- **Advanced Surface Technologies...** SecureWalk™ (top) and SecureGrip (back) create incredible walkability.
- **Improves Project Outcome...** rolls out flat, will not wrinkle causing customer callbacks.
- **Easier Installation...** 33% more coverage per pass across the roof (vs 36" wide rolls).
- **Superior Performance...** designed to perform under extreme weather conditions.
- **Durable...** synthetic construction resists tearing during roof installation - UV stabilized to resist UV degradation up to 60 days.

Description

CMI SecureGripPRO™ Synthetic Roof Deck Protector is a synthetic roof underlayment designed and manufactured to replace asphalt saturated #15 felt in sloped roof system construction.

Uses

A superior performing roofing underlayment used beneath fiberglass and asphalt shingles, shakes, stone coated steel roofing shingles, synthetic tile, synthetic slate or sloped installations of standing seam metal panels.

Storage

Always store rolls upright on pallets (or in the cradled pallet they are shipped on) and in a dry protected area.

Availability

SecureGrip Synthetic Underlayments are available throughout the United States. Check with your local representative for product availability.



SPECIFICATIONS (meets or exceeds applicable standards)

	Standard	SecureGripPRO
Mech Attached Polymer UDL	ASTM D 8257	pass
Permeability	ASTM E96	.06 perms
Water Transmission	ASTM D4869	pass
Nail Sealability	ASTM D1970	pass
Pliability	ASTM D226	pass
Tear Strength	ASTM D4533	MD 25 lbs / CD 25 lbs
Tensile Strength	ASTM D751	MD 40 lbs / CD 40 lbs
Elongation	ASTM D751	MD 20% / CD 20%
Wt Per Square	ASTM D5261	2.0 lbs
Nominal Thickness	ASTM D5261	6.5 mils
Range of Temperature		- 40°F to 240°F
Fire Rating UL Class A	ASTM E108	pass

COMPLIANCE: CODES

Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV

Performance characteristics meet or exceed ASTM D226 – Type I, II

Tested in accordance with ICC-AC-207- UV Exposure – 60 days

U.L. Classified as a Prepared Roofing Accessory

Meets the requirements of ICC-AC-188 – Intertek / WH #CCRR 1045

FBC Approved - #FL18374

TDI Listed – CCRR # 1045

Miami-Dade County approved

PHYSICAL INFORMATION

Per Roll	48" X 250'	Rolls Per Pallet	64 rolls
Material Per Roll	1000 sq. ft.	Wt Per Pallet	1,350 lbs
Squares Per Roll	10 squares	Wt Per 100 sq. ft.	2.0 lbs
Weight Per Roll	20 lbs	Limited Warranty	20 years

