

# X-WEATHER WARRIOR BLACK

*"An Exceptional Synthetic Underlayment Designed to Replace Asphalt Saturated Felts on Your Roofing Projects"*



- **Advanced Engineering...** providing an affordable secondary water-shedding barrier for your shingle roof system.
- **Inorganic Construction...** 100% synthetic construction offers long term moisture protection - doesn't absorb water and is inert to mold growth.
- **Advanced Surface Technologies...** WarriorWalk (top) and WarriorGrip (back) create incredible walkability.
- **Improves Project Outcome...** rolls out flat and does not wrinkle, eliminating customer callbacks.
- **Easier Installation...** 33% more coverage per pass across the roof (vs 36" wide rolls).
- **Superior Performance...** designed to perform under extreme weather conditions.
- **Durable...** synthetic construction resists tearing during roof installation - UV stabilized to resist UV degradation up to 30 days.



*"Non-Woven top and Anti-Slip reverse side offers dynamic steep slope traction"*

## DESCRIPTION

**Xtreme Weather Warrior Black** Synthetic Roof Underlayment is a synthetic roof-deck protection designed and manufactured to replace asphalt saturated felt in sloped roof system construction.

## USES

A cost effective roofing underlayment used beneath fiberglass and asphalt shingles, shakes, stone coated steel roofing shingles and synthetic slate.

## STORAGE

Always store rolls upright on pallets (or in the cradled pallet the rolls are shipped on) and in a dry protected area.

## AVAILABILITY

**Xtreme Weather Warrior Black** Underlayment is available throughout the United States. Check with your local representative.

## COMPLIANCE: CODES

Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV

Performance characteristics meet or exceed ASTM D226 – Type I, II

Meets the requirements of ICC-AC-188 – Intertek

Texas Department of Insurance listed

UV Exposure – 30 days

U.L. Classified as a Prepared Roofing Accessory

## PHYSICAL INFORMATION

Roll Size: 48" X 250'

Material Per Roll: 1000 sq. ft.

Squares Per Roll: 10 squares

Weight Per Roll: 19 lbs

Rolls Per Pallet: 64 rolls

Wt Per Pallet: 1,246 lbs

Wt Per 100 sq. ft.: 1.9 lbs

Limited Warranty: 15 Years

## SPECIFICATIONS (meets or exceeds applicable standards)

	Standard	X-Weather Warrior Black
Permeability	ASTM E96	.06
Water Transmission	ASTM D4869	pass
Pliability	ASTM D226	pass
Tear Strength	ASTM D4533	20 lb MD / 20 lb CD
Tensile Strength	ASTM D751	50 lb MD / 50 lb CD
Elongation	ASTM D751	20% MD / 20% CD
Wt Per Square	ASTM D5261	1.9 lbs
Nominal Thickness	ASTM D5261	6 mils
Range of Temperature		- 40°F to 240°F
Fire Rating UL Class A	ASTM E108	pass