

SecureGripMAX MTS Premium Synthetic Roof Underlayment

Extreme Performance
for a Superior Roof System

"Extreme Performance Roof Deck Protection – Under Metal, Tile, Slate, and Premium Asphalt Shingle Roofs!"

- **Highly Engineered...**extremely strong woven polypropylene fabric with U.V. and water resistive coatings that adds water-shedding redundancy in the roofing system while protecting the structure from damage.
- **100% Inorganic...**synthetic construction offers long term moisture protection - doesn't absorb water, won't rot and is inert to mold growth.
- **Advanced Design Surface Technology...**SecureWalk™ (top) and SecureGrip (back) create extreme walkability.
- **Improves Project Outcome...**rolls out flat and does not wrinkle causing customer callbacks.
- **Easier Installation...**33% more coverage per pass across the roof (vs. 36" wide rolls) - with anti-slip engineered back and walking surfaces for great traction.
- **Superior Performance...**designed to perform in virtually all steep slope roofcovering systems and in extreme weather conditions.
- **Durable...**heavy synthetic construction resists tearing during roof installation - UV stabilized to resist UV degradation up to 6 months.

Description

CMI SecureGrip MTS Synthetic Roof Underlayment is a synthetic roof-deck protection designed and manufactured to replace asphalt saturated 30# felt in sloped roof system construction where toughness and longer exposures may be required.

Uses

A superior performing roofing underlayment used beneath metal, tile, slate as well as under fiberglass and asphalt and metal shingles and shakes.

Storage

Always store rolls upright on pallets (or in the cradled pallet they are shipped on) and in a dry protected area.

Availability

SecureGrip Synthetic Underlayments are available throughout the United States. Check with your local representative for product availability.



SPECIFICATIONS (meets or exceeds applicable standards)

	Standard	SecureGrip MTS
Mech Attached Polymer UDL	ASTM D 8257	pass
Permeability	ASTM E96	< .03 perms
Water Transmission	ASTM D4869	pass
Nail Sealability	ASTM D1970	pass
Pliability	ASTM D226	pass
Tear Strength	ASTM D4533	MD 28 lbs / CD 35 lbs
Tensile Strength	ASTM D751	MD 120 lbs / CD 130 lbs
Puncture Resistance	ASTM D0751	220 PSI
Wt Per Square	ASTM D5261	3.8 lbs
Nominal Thickness	ASTM D5261	20 mils
Range of Temperature		- 40°F to 240°F
Fire Rating UL Class A	ASTM E108	pass

COMPLIANCE: CODES

Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV
 Performance characteristics meet or exceed ASTM D226 – Type I, II
 Tested in accordance with ICC-AC-207- UV Exposure – 365 days
 U.L. Classified as a Prepared Roofing Accessory
 Meets the requirements of ICC-AC-188 – Intertek / WH
 FBC Approved
 TDI Listed
 Miami-Dade County approved

PHYSICAL INFORMATION

Per Roll	48" X 250'	Rolls Per Pallet	25
Material Per Roll	1000 sq. ft.	Wt Per Pallet	1,407 lbs
Squares Per Roll	10 squares	Wt Per 100 sq. ft.	3.8 lbs
Weight Per Roll	38.5 lbs	Limited Warranty	Lifetime

