

# CMI-PAK

## Premium No-Smell™ Roofing Asphalt

CMI-PAK™ with No-Smell technology is brought to you by the US innovators of easy-handle consumable asphalt packaging. For over 65 years, CMI has been providing industry-leading quality roofing products. CMI brings you CMI-PAK with a strong and time-tested protective wrapping eliminating waste and enhancing productivity.



### Your Best Choice For Asphalt is Better...And **EASIER!**

- **100% consumable...** Packaging dissolves, so no wrappers left to clean up afterwards
- **Easier to handle...** Only 40 easy-handle paks per pallet, won't break your installers' backs
- **Safer...** No chopping necessary and no flying asphalt shards
- **Less mess...** No shards to be tracked around the job site or into the building
- **More productivity...** 2000 lbs. per pallet, so less pallets to handle and store

### CMI-PAK has all of the great features you've come to expect from CMI No-Smell Asphalt...

- **Ready to use...** The No-Smell formula is factory mixed to assure maximum effectiveness; no messy or dangerous additives need to be added at the kettle
- **No more odor complaints...** Patented XyClene™ Technology encapsulates the low-end asphaltenes (that produce odor) making the asphalt smell virtually undetectable to workers, building occupants, and neighbors
- **Eliminates scheduling hassles...** Roofing can be performed with No-Smell Asphalt even if building is occupied
- **Superior to competitive technologies...** That only mask the odor (like using perfume) or that have an offensive smell
- **Meets or exceeds ASTM D312-16...** The industry standard for high quality asphalt for built-up roofing
- **Proven performance...** Independently tested to assure long term asphalt integrity
- **Weather Seal™ pallet covering...** Protects your asphalt against ice, water and debris



#### Cartons

- **ASTM and EVT data on every carton...**
- **Superior storability...** UV-resistant protective cover is perfect for the warehouse or at the job site

#### Bulk

- **Improves productivity...** No time wasted melting packaged asphalt
- **Economical...** Less expensive to use (on a total acquisition cost basis) than packaged asphalt



**The Secret Behind Proprietary XyClene™ No-Smell Technology**  
 Unlike cheap imitations, No-Smell Asphalt doesn't just contain a masking agent. Its proprietary XyClene formula is a true odor suppressant. It acts at the molecular level as an oxygen scavenger to retard the release of specific odor-causing compounds. The XyClene formula encapsulates asphaltenes, stopping the evaporation of lighter petroleum molecules and eliminating fumes. It is your best answer to asphalt roofing odors at the kettle, and more importantly, on the roof.

Physical Properties/Specifications (All CMI asphalt meets or exceeds ASTM D312-16 requirements)									
	ASTM Test Method	Type I		Type II		Type III		Type IV	
		Min	Max	Min	Max	Min	Max	Min	Max
Softening Point	D-36	135	151	158	176	185	205	210	225
Flash Point (°F)	D-92	575	-	575	-	575	-	575	-
Penetration, Units:									
at 32°F	D-5	3	-	6	-	6	-	6	-
at 77°F	D-5	18	60	18	40	15	35	12	25
at 115°F	D-5	90	180	-	100	-	90	-	75
Ductility at 77°F, cm	D-113	10	-	3	-	2.5	-	1.5	-
% solubility in trichloroethylene	D-2042	99	-	99	-	99	-	99	-